

High-performance technology for pure coffee perfection.

Professional all-on-one solution with integrated conical burr grinder. Powerful thermal technology with only 2 minutes heat up time. Luxurious design with highest quality matt steel real wood finishes. Integrated precision grinder with 66 grind settings and anti-static technology. Elegant accessories for complete setup with portfilters, milk putcher and tamper. Precision timing for perfect extraction of coffee powder and espresso. Isolated steam wand with handle and 2-hole nozzle for silky milk foam. Equipped with pre-infusion for improved coffee flavour.

LOEWE. was found by the Loewe brothers as Radio Frequenz GmbH in Berlin in 1923. Today we still design, develop and produce consumer electronics - Made in Germany.





High-performance technology for pure coffee perfection.



Powerful thermal technology. Without long warm-up time.

Ready to use. The espresso machine is ready for action in just 2 minutes thanks to the threethermoblock system. Efficient heating of the machine, brewing head and steam system ensure constant performance and temperature control. 15 bar water pressure and a professional pressure gauge for optimum brewing control. Separate thermoblocks for milk vapour and coffee extraction enable simultaneous preparation for individual latte art. The powerful thermoblock technology is not only functional, but also energy-efficient.



Luxurious design. With real wood finishes.

The Loewe aura.pure combines professional features with luxurious design. Made from the highest quality matt steel in basalt grey, with integrated real wood finishes made from pure red oak. An extensive set of elegant and practical accessories completes the design of the espresso machine with portafilter, milk pitcher, tamper, tamper mat, brush and cleaning cloth perfectly matching the design of the espresso machine. A removable 2.5 litre water tank with water filter and removable drip tray ensure easy handling and complete the design of the machine.



The Perfect Duo. Professional all-in-one-solution.

Pure barista feeling. The Loewe aura.pure offers luxurious design with real wood accents and pure convenience thanks to the integrated conical burr grinder. Three thermoblocks ensure fast heating and precise temperature control. Personalise your espresso with the individual pre-infusion function for full flavour potential. All important parameters for espresso preparation can be set at the touch of a button on the display, such as the duration of the grinding process, pre-infusion and espresso extraction.



Integrated precision grinder. With 66 grind settings.

Finest quality for your preferences. The integrated stainless steel conical burr grinder guarantees precise grinding for optimum extraction and pure flavour. Choose from 66 grinding levels, customised to your brewing method from fine grind for espresso to coarse grind for filter coffee or french press. The anti-static technology reduces static electricity and ensures even dispensing directly into the portafilter.



Elegant accessories. For a complete barista setup.

Elegant and practical accessories. The Loewe aura. pure offers a wide range of accessories that turn coffee preparation into an art. The two portafilters single and double shots, along with double wand sieves inserts and real wood handle, accomodate one or two cups. A high-quality tamper with real wood accents matches the design perfectly. The 350ml milk pitcher in basalt grey enables unique latte art. A cleaning cloth, tamper mat, brushes and a blind sieve complete the equipment for a complete barista setup.



Equipped with pre-infusion. For improved coffee flavour.

Espresso machine equipped with pre-infusion for enhanced brewing experience. The Loewe aura.pure features a programmable pre-infusion setting for the soak time of the coffee powder. The process takes place before the actual extraction if the espresso as the ground coffee pwoeder is evenly soaked in water. Choose from 10 settings for improved coffee flavour to ensure a balanced flavour, especially with lighter beans.

High-performance technology for pure coffee perfection.

Home

Power consumption max. (watts): 2350 – 2850W Power consumption standby (watts): <0,5W

Loewe aura.pure



Dimensions in cm: W = width, H = height, PD = product depth, TD = total depth. Technical modifications and errors excepted.

High-performance technology for pure coffee perfection.

Additional information

www.loewe.tv



my Loewe app



Your Loewe contact

We are happy to help personally.

Our Loewe Customer Care Center is here for you: Monday to Friday 09:00 – 17:00 o'clock ccc@loewe.de | 0049 9261 99 500

Your Loewe dealer

Technical Data

Loewe home	aura.pure
Design	
Color	basalt gray
Surface	matt
Housing Material	Painted steel
Material Milk Frother Nozzle	Stainless steel
Brewing Unit	58mm
Material of the Brewing Unit	Chrome
Material of the Cup Tray	Stainless steel
Functions	
Type of Operation	Direct selection buttons, rotary controls
Display Size in Inches	1,5"
Display Technology	LCD Display
Color of Display Illumination	white
Temperature Range	88-96 Degrees Celsius
Pre-infusion	•
Steam Wand for Milk Frothing	•
Passive Heated Cup Warmer	•
Specialties	
Espresso	•
Double Espresso	· · · · · · · · · · · · · · · · ·
Hot Water	
Hot Water	· _ · _ · _ · _ · _ · _ · _ · _ ·
Milk Froth Production	•
Hygiene Standards	
Filter Cartridges	•
Monitoring of Residual Water Tray	•
Technical Features	
Heating System	3 PID Thermoblocks
Number of Heating Circuits	2
Type of Pumps	Vibration pump
Number of Pumps	2
Coffee Extraction Pump Pressure	15 bar
Steam Extraction Pump Pressure	4 bar
Brewing Pressure Gauge	•
Water Tank	•
Water Tank Capacity	2,51
Removable Water Tank	•
Connectivity and Interfaces	
Integrated Grinder	•
Number of Grinding Mechanisms	1
Ionizer / Anti-Static Design	•
Type of Grinding Mechanism	Stainless steel
Number of Grind Settings	66
Speed	
Speed Grinding Discs	1400 U/min.
Grinding Discs	
Grinding Discs Number of Bean Containers	1400 U/min. Stainless steel, 54mm 1
Grinding Discs Number of Bean Containers Bean Container Capacity	1400 U/min. Stainless steel, 54mm
Grinding Discs Number of Bean Containers Bean Container Capacity Connections	1400 U/min. Stainless steel, 54mm 1 200gr
Grinding Discs Number of Bean Containers Bean Container Capacity Connections Mains Voltage AC	1400 U/min. Stainless steel, 54mm 1 200gr 220-240V, 50 Hz
Grinding Discs Number of Bean Containers Bean Container Capacity Connections Mains Voltage AC Power Consumption / Energy Efficiency Class	1400 U/min. Stainless steel, 54mm 1 200gr 220-240V, 50 Hz 2350-2850W/ —
Grinding Discs Number of Bean Containers Bean Container Capacity Connections Mains Voltage AC Power Consumption / Energy Efficiency Class Standby Power	1400 U/min. Stainless steel, 54mm 1 200gr 220-240V, 50 Hz 2350-2850W/ — <0.5W
Grinding Discs Number of Bean Containers Bean Container Capacity Connections Mains Voltage AC Power Consumption / Energy Efficiency Class Standby Power Length of Power Cord	1400 U/min. Stainless steel, 54mm 1 200gr 220-240V, 50 Hz 2350-2850W/ — <0.5W
Grinding Discs Number of Bean Containers Bean Container Capacity Connections Mains Voltage AC Power Consumption / Energy Efficiency Class Standby Power	1400 U/min. Stainless steel, 54mm 1 200gr 220-240V, 50 Hz 2350-2850W/ — <0.5W
Grinding Discs Number of Bean Containers Bean Container Capacity Connections Mains Voltage AC Power Consumption / Energy Efficiency Class Standby Power Length of Power Cord Compliance Markings	1400 U/min. Stainless steel, 54mm 1 200gr 220-240V, 50 Hz 2350-2850W/ — <0.5W
Grinding Discs Number of Bean Containers Bean Container Capacity Connections Mains Voltage AC Power Consumption / Energy Efficiency Class Standby Power Length of Power Cord Compliance Markings Dimensions	1400 U/min. Stainless steel, 54mm 1 200gr 220-240V, 50 Hz 2350-2850W/ — <0.5W
Grinding Discs Number of Bean Containers Bean Container Capacity Connections Mains Voltage AC Power Consumption / Energy Efficiency Class Standby Power Length of Power Cord Compliance Markings Dimensions Weight (approx.kg)	1400 U/min. Stainless steel, 54mm 1 200gr 220-240V, 50 Hz 2350-2850W/ — <0.5W
Grinding Discs Number of Bean Containers Bean Container Capacity Connections Mains Voltage AC Power Consumption / Energy Efficiency Class Standby Power Length of Power Cord Compliance Markings Dimensions Weight (approx.kg) W x H x D (approx.cm)	1400 U/min. Stainless steel, 54mm 1 200gr 220-240V, 50 Hz 2350-2850W/ — <0.5W
Grinding Discs Number of Bean Containers Bean Container Capacity Connections Mains Voltage AC Power Consumption / Energy Efficiency Class Standby Power Length of Power Cord Compliance Markings Dimensions Weight (approx. kg) W x H x D (approx. cm) Scope of Delivery	1400 U/min. Stainless steel, 54mm 1 200gr 220-240V, 50 Hz 2350-2850W/ — <0.5W
Grinding Discs Number of Bean Containers Bean Container Capacity Connections Mains Voltage AC Power Consumption / Energy Efficiency Class Standby Power Length of Power Cord Compliance Markings Dimensions Weight (approx.kg) W x H x D (approx.cm)	1400 U/min. Stainless steel, 54mm 1 200gr 220-240V, 50 Hz 2350-2850W/ — <0.5W
Grinding Discs Number of Bean Containers Bean Container Capacity Connections Mains Voltage AC Power Consumption / Energy Efficiency Class Standby Power Length of Power Cord Compliance Markings Dimensions Weight (approx. kg) W x H x D (approx. cm) Scope of Delivery	1400 U/min. Stainless steel, 54mm 1 200gr 220-240V, 50 Hz 2350-2850W/ — <0.5W
Grinding Discs Number of Bean Containers Bean Container Capacity Connections Mains Voltage AC Power Consumption / Energy Efficiency Class Standby Power Length of Power Cord Compliance Markings Dimensions Weight (approx. kg) W x H x D (approx. cm) Scope of Delivery 1-Spout Portafilter	1400 U/min. Stainless steel, 54mm 1 200gr 220-240V, 50 Hz 2350-2850W/ — <0.5W
Grinding Discs Number of Bean Containers Bean Container Capacity Connections Mains Voltage AC Power Consumption / Energy Efficiency Class Standby Power Length of Power Cord Compliance Markings Dimensions Weight (approx.kg) W x H x D (approx.cm) Scope of Delivery 1-Spout Portafilter 2-Spout Portafilter 2-Spout Portafilter Blind Filter	1400 U/min. Stainless steel, 54mm 1 200gr 220-240V, 50 Hz 2350-2850W/ — <0.5W
Grinding Discs Number of Bean Containers Bean Container Capacity Connections Mains Voltage AC Power Consumption / Energy Efficiency Class Standby Power Length of Power Cord Compliance Markings Dimensions Weight (approx.kg) W x H x D (approx.cm) Scope of Delivery 1-Spout Portafilter 2-Spout Portafilter Blind Filter Cleaning Brush	1400 U/min. Stainless steel, 54mm 1 200gr 220-240V, 50 Hz 2350-2850W/ — <0.5W
Grinding Discs Number of Bean Containers Bean Container Capacity Connections Mains Voltage AC Power Consumption / Energy Efficiency Class Standby Power Length of Power Cord Compliance Markings Dimensions Weight (approx. kg) W x H x D (approx. cm) Scope of Delivery 1-Spout Portafilter 2-Spout Portafilter Blind Filter Cleaning Brush Tamper	1400 U/min. Stainless steel, 54mm 1 200gr 220-240V, 50 Hz 2350-2850W/ — <0.5W
Grinding Discs Number of Bean Containers Bean Container Capacity Connections Mains Voltage AC Power Consumption / Energy Efficiency Class Standby Power Length of Power Cord Compliance Markings Dimensions Weight (approx. kg) W x H x D (approx. cm) Scope of Delivery 1-Spout Portafilter Sind Filter 2-Spout Portafilter Blind Filter Cleaning Brush Tamper Tamper Pad	1400 U/min. Stainless steel, 54mm 1 200gr 220-240V, 50 Hz 2350-2850W/ — <0.5W
Grinding Discs Number of Bean Containers Bean Container Capacity Connections Mains Voltage AC Power Consumption / Energy Efficiency Class Standby Power Length of Power Cord Compliance Markings Dimensions Weight (approx.kg) W x H x D (approx.cm) Scope of Delivery 1-Spout Portafilter 2-Spout Portafilter Blind Filter Cleaning Brush Tamper Tamper Pad Barista Cloth	1400 U/min. Stainless steel, 54mm 1 200gr 220-240V, 50 Hz 2350-2850W/ <0.5W
Grinding Discs Number of Bean Containers Bean Container Capacity Connections Mains Voltage AC Power Consumption / Energy Efficiency Class Standby Power Length of Power Cord Compliance Markings Dimensions Weight (approx.kg) W x H x D (approx.cm) Scope of Delivery 1-Spout Portafilter Blind Filter Cleaning Brush Tamper Pad Barista Cloth Milk Pitcher	1400 U/min. Stainless steel, 54mm 1 200gr 220-240V, 50 Hz 2350-2850W/ — <0.5W
Grinding Discs Number of Bean Containers Bean Container Capacity Connections Mains Voltage AC Power Consumption / Energy Efficiency Class Standby Power Length of Power Cord Compliance Markings Dimensions Weight (approx.kg) W x H x D (approx.cm) Scope of Delivery 1-Spout Portafilter 2-Spout Portafilter Blind Filter Cleaning Brush Tamper Tamper Pad Barista Cloth Milk Pitcher Optional accessories	1400 U/min. Stainless steel, 54mm 1 200gr 220-240V, 50 Hz 2350-2850W/ <0.5W
Grinding Discs Number of Bean Containers Bean Container Capacity Connections Mains Voltage AC Power Consumption / Energy Efficiency Class Standby Power Length of Power Cord Compliance Markings Dimensions Weight (approx. kg) W x H x D (approx. cm) Scope of Delivery 1-Spout Portafilter 2-Spout Portafilter Blind Filter Cleaning Brush Tamper Pad Barista Cloth Milk Pitcher Optional accessories Tamper Station	1400 U/min. Stainless steel, 54mm 1 200gr 220-240V, 50 Hz 2350-2850W/ <0.5W
Grinding Discs Number of Bean Containers Bean Container Capacity Connections Mains Voltage AC Power Consumption / Energy Efficiency Class Standby Power Length of Power Cord Compliance Markings Dimensions Weight (approx.kg) W x H x D (approx.cm) Scope of Delivery 1-Spout Portafilter 2-Spout Portafilter Blind Filter Cleaning Brush Tamper Tamper Pad Barista Cloth Milk Pitcher Optional accessories	1400 U/min. Stainless steel, 54mm 1 200gr 220-240V, 50 Hz 2350-2850W/ <0.5W
Grinding Discs Number of Bean Containers Bean Container Capacity Connections Mains Voltage AC Power Consumption / Energy Efficiency Class Standby Power Length of Power Cord Compliance Markings Dimensions Weight (approx. kg) W x H x D (approx. cm) Scope of Delivery 1-Spout Portafilter 2-Spout Portafilter Blind Filter Cleaning Brush Tamper Pad Barista Cloth Milk Pitcher Optional accessories Tamper Station	1400 U/min. Stainless steel, 54mm 1 200gr 220-240V, 50 Hz 2350-2850W/ <0.5W

• = available, • = optional, — = not available

Technical changes, delivery options, errors and price changes reserved. All product and company names are trademarksTM or registered[®] trademarks of their respective owners. Their use does not imply any affiliation with or endorsement by these companies. Digital services and content (e.g., apps) and server platforms are provided by third parties. Available for download in the App Store. Observe the terms of use of the third party on the device. The provision, availability (including in certain territories), updating and termination of the provision of this digital content and services on the device are the sole discretion of the third party. Some services may not be available at the time of purchase of this product. Internet access required. Separate (paid) subscriptions and/or membership required. Ultra HD and HDR availability subject to subscription plan, internet service, device features and content availability.